

**Single Phase/ Monofásico(110-240V)**



**DESCRIPTION**

- \* 4 stroke air-cooled diesel engine
- \* Low oil alarm protection with automatic shut off engine
- \* Big muffler for low noise level
- \* AVR, Automatic voltage regulator
- \* Large-capacity fuel tank, run longer

**Control Panel**

- \* Overload current protection
- \* DC 12V output 8.3A
- \* Earth connection
- \* 2 sockets for single phase & voltmeter

**Optional:**

- \* Remote control ; ATS box; Emergency stop button

**DESCRIPCION**

- \* Motor diesel de 4 tiempos refrigerado por aire
- \* Alarma de seguridad para nivel bajo de aceite con apagado automático del motor
- \* Gran aislante para bajo nivel de ruido
- \* AVR, regulador automático de voltaje
- \* Depósito de combustible de gran capacidad para mayor autonomía

**Panel de control**

- \* Protección contra las sobrecargas
- \* DC 12V salida 8,3 A
- \* Conexión a tierra
- \* Dos tomas de corriente para monofásico y voltmetro

**Opcional:**

- \* Control remoto, Caja ATS, botón de parada de emergencia

MODEL / MODELO	KD5000S		KD6000S		KD6500S		KD7500S		KD8000S	
Frequency / Frecuencia (Hz)	50	60	50	60	50	60	50	60	50	60
Max. AC output / Potencia máxima (kW)	<b>4.6</b>	<b>5.0</b>	<b>5.0</b>	<b>5.5</b>	<b>5.5</b>	<b>5.8</b>	<b>6.0</b>	<b>6.6</b>	<b>6.5</b>	<b>6.7</b>
Cont. AC output / Potencia media (kW)	4.2	4.6	4.5	5	5	5.3	5.5	6	6	6.2
Voltage / Voltaje (V)	110-240									
D.C. output / D.C. salida (V-A)	12 / 8.3									
Power Factor / Factor de potencia	1									
Fuel Tank Capacity / Capacidad combustible (L)	16									
Continuous working time / Autonomía (h)	7		6.6		6.6		7		7	
Noise at 7m / Ruido a 7m dB (A)	71									
Engine Model / Modelo Motor	<b>D186E</b>		<b>D186FAE</b>		<b>D188E</b>		<b>D188E</b>		<b>D192E</b>	
Displacement / Capacidad (cc)	406		418		474		474		498	
Engine Speed / Velocidad motor (rpm)	3000	3600	3000	3600	3000	3600	3000	3600	3000	3600
Lube Oil Capacity / Capacidad aceite (l)	1.65		1.65		1.65		1.65		1.65	
Starting system / Sistema de arranque	Electric start / <b>Eléctrico</b>									
Dimension and Weight / Dimensiones y Peso										
Dimensions / Dimensiones (LxWxH) (mm)	900*520*700		900*520*700		900*520*700		900*520*700		960*560*710	
Net Weight / Peso Neto (Recoil) (kg)	140		150		154		155		164	
Gross weight / Peso Bruto (Recoil) (kg)	155		165		169		170		180	
20'40'40HQ' Quantity Per Container / Unidades por contenedor 20'40'40HQ'	72/156/156		72/156/156		72/156/156		72/156/156		72/156/156	