



Diesel Welder & Generator
Motosoldadoras diesel
KDW200ARE



Diesel Welder & Generator
Motosoldadoras diesel
KDW300ARS



KDW300ARS
Powered by V twin DV292E
diesel engine (25HP)

Con motor diesel bicilindrico
en V DV292E(25HP)

DESCRIPTION

- * AVR, Automatic voltage regulator
- * Low oil alarm protection with automatic shut off engine

Control Panel

- * Adjusting welding current 0-300A
- * 2 sockets for single phase & voltmeter

Optional:

- * Welding Kit: Mask, Clamps, Cables 5m

DESCRIPCION

- * AVR, regulador automático de voltaje
- * Alarma de seguridad para nivel bajo de aceite con apagado automático del motor

Panel de control

- * Ajuste de corriente de soldadura 0-300A
- * Dos tomas de corriente para monofásico y voltmetro

Opcional:

- * Kit de soldadura: Máscara, Pinzas, Cables

MODEL / MODELO	KDW180ARE		KDW300ARS	
Frequency / Frecuencia (Hz)	50	60	50	60
Max. AC output / Potencia máxima (kw)	2	2.2	4.2	4.4
Cont. AC output / Potencia media (kw)	1.8	2	4	4.2
Voltage / Voltaje (V)	110-240			
Operating welding voltage Voltaje operativo de soldadura (V)	22-26		30	30
Operating current / Corriente operativa (A)	50-120	50-130	50-260	50-270
Max.Arcing current / Corriente Máxima (A)	180		300	
Power Factor / Factor de potencia	1		1	
Fuel Tank Capacity / Capacidad Combustible (L)	12.5		60	
Continuous working time / Autonomía (h)	5.3		12.5	
Noise at 7m / Ruido a 7m dB (A)	82		69	
Engine Model / Modelo Motor	Diesel Engine Motor Diesel D186FAE		Diesel Engine Motor Diesel DV290E	
Displacement / Capacidad (cc)	418		954	
Engine Speed / Velocidad (rpm)	3000	3600	3000	3600
Lube Oil Capacity / Capacidad Aceite (L)	1.65		3	
Starting system / Sistema Arranque	Electric start / <i>Eléctrico</i>			
Dimension and Weight / Dimensiones y Peso				
Dimensions / Dimensiones (LxWxH) (mm)	740*475*605		1160*675*945	
Net Weight / Peso Neto (kg)	125		320	
Gross weight (Recoil) / Peso Bruto (Recoil) (kg)	128		360	
20'40'40HQ' Quantity Per Container Unidades por contenedor 20'40'40HQ'	48/96/120		32/68/68	