

Single Phase (110-240V) / Three Phase (220/380V; 230/400V) ;
Monofásico (110-240V) / Trifásico (220/380V ; 230/400V)

DESCRIPTION

- * Equipped with wheels, electric start and battery
- * 4 stroke air-cooled twin cylinders 20HP gasoline engine
- * Low oil alarm protection with automatic shut off engine
- * Big muffler for low noise level, AVR, Automatic voltage regulator
- * Large-capacity fuel tank, run longer
- * Overload current protection, DC 12V output 8.3A, Earth connection
- * 2 sockets for single phase , 1 socket for three phase & voltmeter

Optional:

- * Remote control ; ATS box; Emergency stop button; Digital display panel



Open Type / Abiertos

Powered by V twin cylinders
gasoline engine G740E (22HP)
Con motor gasolina bicilindrico
en V GP740E (22HP)

DESCRIPCION

- * Equipado con ruedas, arranque eléctrico y batería
- * Motor gasolina de 4 tiempos refrigerado por aire de 20 HP
- * Alarma de bajo nivel de aceite y protección con apagado del motor
- * Gran asilante para menor nivel de ruido, AVR, regulador automático de voltaje
- * Depósito de combustible de gran capacidad para mayor autonomía
- * Protección contra sobrecargas, DC 12V salida 8,3 A, conexión a tierra
- * Dos tomas de corriente para monofásico, una salida de corriente para trifásico y voltímetro

Opcional:

- * Control remoto, Caja ATS, botón de parada de emergencia, panel digital



Silent Type / Silenciosos

MODEL / MODELO	KG15000E		KG15000E-3		KG15000S		KG15000S-3	
Frequency / Frecuencia (Hz)	50	60	50	60	50	60	50	60
Voltage / Voltaje (V)	110 - 240		220/380 ; 230/400		110 - 240		220/380 ; 230/400	
Max. AC output / Potencia máxima (kw)	12kW	13kW	15kVA	16.25kVA	12kW	13kW	15kVA	16.25kVA
Cont. AC output / Potencia media (kw)	11kW	12kW	13.75kVA	15kVA	11kW	12kW	13.75kVA	15kVA
D.C. output / D.C. salida (V-A)	12V - 6A		12V - 6A		12V - 6A		12V - 6A	
Fuel Tank Capacity / Capacidad combustible (L)	25		25		25		25	
Continuous working time / Autonomia (h)	4.2		4.2		5.5		5.5	
Noise at 7m / Ruido a 7m dB (A)	84		84		66		66	
Engine Model / Modelo de motor	G740E		G740E		G740E		G740E	
Starting system / Sistema de arranque	Electric start / <i>Eléctrico</i>							
Lube Oil Capacity / Capacidad aceite (L)	1.5		1.5		1.5		1.5	
Dimension and Weight / Dimensiones y Peso								
Dimensions / Dimensiones (LxWxH) (mm)	930*555*580		930*555*580		990*640*945		990*640*945	
Net Weight / Peso Neto (kg)	144		155		234		244	
Gross weight (Recoil) / Peso Bruto (Recoil) (kg)	160		170		250		260	
20'40'40HQ' Quantity Per Container / Unidades por contenedor 20'40'40HQ'	63/132/132		63/132/132		34/72/72		34/72/72	