

Diesel Cast Iron Pump 2"/3"  
 Motobombas Diesel Fundición 2"/3"  
 Diesel Trash Pump 3"/6"  
 Motobombas Diesel Aguas Sucias 3"/6"

**KRAFTCROME**  
 PROFESSIONAL QUALITY TOOLS

## DESCRIPTION

- \* 4 stroke air-cooled diesel engine
- \* Low oil alarm protection with automatic shut off engine
- \* High quality Mechanical seal for all pumps

### Optional:

- \* Electric start (E), Battery (B), Wheel kits (W), Big fuel tank (L)

## DESCRIPCION

- \* Motor diesel de 4 tiempos refrigerado por aire
- \* Alarma de seguridad para nivel bajo de aceite con apagado automático del motor
- \* Sello mecanico de alta calidad

### Opcional:

- \* Eléctrico(E), Batería(B), Kit de ruedas (W), Tanque grande (L)



DCP50 / DCP80



DTP80



DTP150L

MODEL / MODELO	DCP50	DCP80	DTP80	DTP150L
	Cast Iron Pump / <i>Motobombas Fundición</i>		Trash Pump / <i>Motobombas Aguas Sucias</i>	
Inlet / Entrada	50mm(2")	80mm(3")	80mm(3")	150mm(6")
Outlet / Salida	50mm(2")	80mm(3")	80mm(3")	150mm(6")
Max. Capacity / Caudal máximo (m <sup>3</sup> / hr)	30	26	50	130
Max discharge head / Altura máxima (m)	65	65	25	18
Max. Suction Head / Altura máxima succión (m)	8	8	8	6
Engine Model / Modelo del motor	D186	D186	D178	D290E
Type / Tipo	4-stroke, Air-cooled Diesel / <i>4 tiempos, Diesel</i>			Twin-cylinder, Diesel <i>Doble cilindro, Diesel</i>
Max output / Max. Potencia (hp / rpm)	10.0 / 3600	10.0 / 3600	6.0 / 3600	20.0 / 3600
Engine Displacement / Capacidad del motor (cc)	406	406	296	954
Fuel tank capacity / Capacidad combustible (L)	5.5	5.5	3.5	30
Continuous working time / Autonomía (h)	2.5	2.5	2.8	7.5
Starting system / Sistema arranque	Recoil start; Electric start as option / <i>Recoil ; Eléctrico como opcional</i>			Electric start / <i>Eléctrico</i>
Dimensions and Weight / Dimensiones y pesos				
Net weight / Peso Neto (kg)	64	72.5	48	150
Gross weight / Peso bruto (kg)	66	74	50	165
Dimensions / Dimensiones (L*W*H)(mm)	545*480*605	545*475*605	590*450*530	920*660*820
20'40'40HQ' Quantity Per Container 20'40'40HQ' Unidades por contenedor	126/264/352	126/264/352	168/352/352	40/86/129